

Apollo Entrance Polycarbonate Clad

The Apollo polycarbonate entrance canopy is one of our most popular off the shelf design of polycarbonate Entrance Canopies. The Apollo is supported from 2 or more columns and is entirely freestanding. The trellis type beams give the opportunity to position the column legs further to the rear or front of the canopy cantilevering the roof out. As standard the roof is clad in solid sheet polycarbonate.



Warranties

Framework - 25 years

Polycarbonate Cladding - 10 years against discolouration through sunlight



The maximum width for the Apollo is around 5m but each canopy as fabricated to suit the clients requirements.



Applicable Standards

BS6399 Pt.2 - Wind & Snow Loadings; BS5950 - Structural Use of Steelwork in Buildings



Roof Shape

Low Rise Barrel Vault



Solid Polycarbonate

Flame Retardant (Class 1) Solid Sheet Clear Polycarbonate with a 10 year guarantee against discolouration from sunlight



Cladding Fixing

Two part Aluminium Glazing Bar with rubber gaskets to allow for thermal expansion of the roofing sheets and secure fixing



Standard Finish Shot blast, zinc sprayed and polyester powder coated to any standard RAL or BS colour



Rainwater Goods

Colour coded Aluminium gutters included as standard to all eaves sides, with down pipes terminating at ground level



Foundation Fixings

Cast in-situ anchor bolts into concrete foundation pads typically 800mm square x 600mm deep













Call 01622 873900 email sales@clovis-canopies.com or visit our website www.clovis-canopies.com

